

Product Name :
Vertical Laboratory Shaker

Product Code :
MED-PTH0012



Description :

Vertical Laboratory Shaker

Technical Specification :

The original technology of the original single-axis drive balance device 1(patent type: a single-axis drive swing balance mechanism; patent to ensure minimum energy consumption and noise.
Vertical double-layer structure, small footprint, large bottle capacity and double performance.
The oscillation frequency can be extended over a wide range to 50-300 rpm.
Intelligent sound and light alarm environment scanning microprocessor controller.
The LCD large-screen backlit LCD display double displays each set parameter and measured parameter.
safe, fluorine-free refrigeration system that meets international environmental requirements.
Run the parameter memory function to avoid cumbersome operations.
AC induction long life motor design, wide speed regulation, constant torque, constant speed, no carbon brush, maintenance free.
Over-temperature sound and light alarm function, motor overheating, temperature out of control, abnormal over-temperature instrument automatically cut off their respective power supply.
With power-off recovery function, after the external power supply suddenly loses power and calls again, the device can automatically resume operation according to the original setting program.
The line that controls the acceleration ensures that the shaker is slowly started and smoothly accelerated to ensure the safety of the experimental samples.
The streamlined luxury machine model with rich aesthetic design concept, electrostatic spray box, large screen tempered glass window.
Timing setting up to 500 hours, and sound and light alarm
Adapt to the increasing trend of sample processing in modern laboratories and the mass production of modern bioengineering.

The front door opening design allows the shaker to be more flexible than turning the door shaker up.
 Available in both temperature and low temperature ranges.
 Efficient drive Makeda and refrigeration control, ultra-low energy consumption.
 The transparent viewing window and built-in lighting design make it easy to view samples at any time.
 Simultaneous observation of temperature, oscillation speed, time
 Application range
 Cell culture
 Solubility test
 Extraction experiment
 Diagnostic test
 Mixing samples
 Bacterial suspension preparation
 Dyeing and bleaching
 Elution process
 Hybrid experiment
 control method: P.I.D(Microcomputer environment scanning micro processing chip)
 Display method: LCD (Large screen LCD dual display)
 Cyclic mode: Forced convection
 Oscillation mode: Rotary oscillation
 Drive mode: Single-axis balancing device (Chinese patent)
 Environmental requirements: Temperature 25 ° C, humidity 20% -90%
 Opening method: Single door
 Temperature control range: Room temperature +5?-60? 4-60?
 Temperature accuracy: $\pm 0.1^{\circ}\text{C}$
 Temperature uniformity: $\pm 1^{\circ}\text{C}$
 Performance: Frequency Range 30-300rpm
 Rotation accuracy:
 Pendulum amplitude: $\pm 25\text{mm}$
 security function: Upper and lower temperature deviation alarm; upper- and lower-line speed deviation alarm,
 independent over-temperature protector; open door stop protection; leakage protection, chiller overload
 protection.
 Accessory function: Speed storage, call recovery, parameter memory, temperature speed correction, clock
 display, room temperature / measured temperature double display.
 Programming function: Repeat, step, eight-segment curve programming settings.
 The refrigerant: CFC-Free (134A) fluorine-free safety refrigeration system
 Cooler: 200W
 Heater: 500W
 Timing range: 0-999.99h/ Sustainable
 Standard sizes: Rocker size 500*350(mm)
 Number of rocking plates: Two
 Gross weight: 150kg 165kg
 Inner cavity size: 600*440*650H (mm)
 power: 600W 830W
 power supply: AC 200-240V 50-60HZ
 Materia: Motor 120W inverter motor
 Inner cavity material: High quality imported stainless steel mirror panel
 box Materia: High quality channel steel, angle steel, cold rolled steel plate

Medical Hospital Equipments Manufacturers

Website: [SITE](#).

NAUGRA[®]